



# Shandong XSY Bearing Co., Ltd.

## NTN UCFX20-400D1 Flange Block Bearings



Bearing No. UCFX20-400D1

UCFX20-400D1 Bearing 2D drawings and 3D CAD models

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	20.028
EAN	4547359217865
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Set Screw
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1 Inch
Relubricatable	Yes
Insert Part Number	UCX20-400D1
Seals	Single Lip Land Riding
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch - Metric	Inch
Long Description	4 Bolt Square Flange Block; 4" Bore; 11.7" Bolt Circle; 8-5/16" Bolt Spacing; 1 Piece Solid; Set Screw Mount; Cast Iron; Ball Bearing; 4-5/8" Length Thru Bore; Relubricatable; Sing
Other Features	Single Row   Medium Duty



## Shandong XSY Bearing Co., Ltd.

	Wide Inner Race   Has Flinger
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	UCFX20-400D1
Weight / LBS	37
Cartridge Pilot Diameter	0 Inch   0 Millimeter
D	4.626 Inch   117.5 Millimeter
Bolt Spacing	8.313 Inch   211.15 Millimeter
d	4 Inch   101.6 Millimeter
Cartridge Pilot Depth	0 Inch   0 Millimeter
Nominal Bolt Circle Diameter Round	11.7 Inch   297 Millimeter
bore diameter:	4.0000 in
radial dynamic load capacity:	29910 lb
bolt center-to-center length:	8.3125 in
radial static load capacity:	23620 lb
overall length/diameter:	10.5625 in
seal type:	Contact with Flinger
bore type:	Round
length through bore:	5-1/64 in
duty type:	Medium Duty
finish/coating:	Uncoated
mounting type:	Four-Bolt Flange
lubrication type:	Lubrication Fitting
housing material:	Cast Iron



## Shandong XSY Bearing Co., Ltd.

series:	UCFX
locking device:	Set Screw
standards met:	ISO, AFBMA
expansion type:	Non-Expansion Bearing (Fixed)
replacement bearing:	UCX20-400D1